

Study guide: Scientific software engineering; wave equation model

Hans Petter Langtangen^{1,2}

Center for Biomedical Computing, Simula Research Laboratory¹

Department of Informatics, University of Oslo²

Oct 20, 2015

Migrating loops to Cython

- Vectorization: 5-10 times slower than pure C or Fortran code
- Cython: extension of Python for translating functions to C
- Principle: declare variables with type

Declaring variables and annotating the code

Pure Python code:

```
def advance_scalar(u, u_1, u_2, f, x, y, t,
                   n, Cx2, Cy2, dt2, D1=2, D2=1):
    Ix = range(0, u.shape[0]); Iy = range(0, u.shape[1])
    for i in Ix[1:-1]:
        for j in Iy[1:-1]:
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = D1*u_1[i,j] - D2*u_2[i,j] + \
                     Cx2*u_xx + Cy2*u_yy + dt2*f(x[i], y[j], t[n])
```

- Copy this function and put it in a file with .pyx extension.
- Add type of variables:
 - function(a, b) → cdef function(int a, double b)
 - v = 1.2 → cdef double v = 1.2
 - Array declaration:
np.ndarray[np.float64_t, ndim=2, mode='c'] u

Cython version of the functions

```
import numpy as np
cimport numpy as np
cimport cython
ctypedef np.float64_t DT # data type

@cython.boundscheck(False) # turn off array bounds check
@cython.wraparound(False) # turn off negative indices (u[-1,-1])
cpdef advance(cdouble Cx2, cdouble Cy2, cdouble dt2):
    import numpy as np
    cdef double u_xx, u_yy
    Nx = u.shape[0]-1
    Ny = u.shape[1]-1
    for i in xrange(1, Nx):
        for j in xrange(1, Ny):
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = 2*u_1[i,j] - u_2[i,j] + \
                     Cx2*u_xx + Cy2*u_yy + dt2*f[i,j]
```

Note: from now in we skip the code for setting boundary values

Visual inspection of the C translation

See how effective Cython can translate this code to C:

Terminal> cython -a wave2D_u0_loop_cy.pyx

Load wave2D_u0_loop_cy.html in a browser (white lines indicate code that was successfully translated to pure C, while yellow lines indicate code that is still in Python):

```
Line numbers are shown above the code
1: cimport numpy as np
2: cdef np.float64_t Cx2, Cy2
3: cdef double dt2, t_0T # data type
4: cdef np.ndarray[np.float64_t, ndim=2, mode='c'] u
5: cdef np.ndarray[np.float64_t, ndim=2, mode='c'] u_1, u_2
6: cdef np.ndarray[np.float64_t, ndim=2, mode='c'] u_xx, u_yy
7: cdef np.ndarray[np.float64_t, ndim=2, mode='c'] f
8: cdef int Nx, Ny, i, j
9: cdef double u_xx, u_yy
10: Nx = u.shape[0]-1
11: Ny = u.shape[1]-1
12: for i in xrange(1, Nx):
13:     for j in xrange(1, Ny):
14:         u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
15:         u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
16:         u[i,j] = 2*u_1[i,j] - u_2[i,j] + \
17:                  Cx2*u_xx + Cy2*u_yy + dt2*f[i,j]
```

Can click on wave2D_u0_loop_cy.c to see the generated C code...

Building the extension module

- Cython code must be translated to C
- C code must be compiled
- Compiled C code must be linked to Python C libraries
- Result: C extension module (.so file) that can be loaded as a standard Python module
- Use a setup.py script to build the extension module

```
from distutils.core import setup
from distutils.extension import Extension
from Cython.Distutils import build_ext

cymodule = 'wave2D_u0_loop_cy'
setup(
    name=cymodule,
    ext_modules=[Extension(cymodule, [cymodule + '.pyx'],)],
    cmdclass={'build_ext': build_ext},
)
```

Terminal> python setup.py build_ext --inplace

Calling the Cython function from Python

```
import wave2D_u0_loop_cy
advance = wave2D_u0_loop_cy.advance
...
for n in It[1:-1]:  
    f_a[:, :] = f(xv, yv, t[n])      # precompute, size as u
    u = advance(u, u_1, u_2, f_a, x, y, t, Cx2, Cy2, dt2)
```

Efficiency:

- 120 × 120 cells in space:
 - Pure Python: 1370 CPU time units
 - Vectorized numpy: 5.5
 - Cython: 1
- 60 × 60 cells in space:
 - Pure Python: 1000 CPU time units
 - Vectorized numpy: 6
 - Cython: 1

Migrating loops to Fortran

- Write the advance function in pure Fortran
- Use f2py to generate C code for calling Fortran from Python
- Full manual control of the translation to Fortran

The Fortran subroutine

```
subroutine advance(u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny)
integer Nx, Ny
real*8 u(0:Nx, 0:Ny), u_1(0:Nx, 0:Ny), u_2(0:Nx, 0:Ny)
real*8 f(0:Nx, 0:Ny), Cx2, Cy2, dt2
integer i, j
Cf2py intent(in, out) u
C Scheme at interior points
do j = 1, Ny-1
    do i = 1, Nx-1
        u(i,j) = 2*u_1(i,j) - u_2(i,j) +
        & Cx2*(u_1(i-1,j)) - 2*u_1(i,j) + u_1(i+1,j) +
        & Cy2*(u_1(i,j-1)) - 2*u_1(i,j) + u_1(i,j+1)) +
        & dt2*f(i,j)
    end do
end do
```

Note: Cf2py comment declares u as input argument and return value back to Python

Building the Fortran module with f2py

```
Terminal> f2py -m wave2D_u0_loop_f77 -h wave2D_u0_loop_f77.pyf \
          --overwrite-signature wave2D_u0_loop_f77.f
Terminal> f2py -c wave2D_u0_loop_f77.pyf --build-dir build_f77 \
          -DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_f77.f
```

f2py changes the argument list (!)

```
>>> import wave2D_u0_loop_f77
>>> print wave2D_u0_loop_f77.__doc__
This module 'wave2D_u0_loop_f77' is auto-generated with f2py.....
Functions:
    u = advance(u,u_1,u_2,f,Cx2,cy2,dt2,
                nx=(shape(u,0)-1),ny=(shape(u,1)-1))
```

- Array limits have default values
- Examine doc strings from f2py!

How to avoid array copying

- Two-dimensional arrays are stored row by row in Python and C
- Two-dimensional arrays are stored column by column in Fortran
- f2py takes a copy of a numpy (C) array and transposes it when calling Fortran
- Such copies are time and memory consuming
- Remedy: declare numpy arrays with Fortran storage

```
order = 'Fortran' if version == 'f77' else 'C'
u = zeros((Nx+1,Ny+1), order=order)
u_1 = zeros((Nx+1,Ny+1), order=order)
u_2 = zeros((Nx+1,Ny+1), order=order)
```

Option -DF2PY_REPORT_ON_ARRAY_COPY=1 makes f2py write out array copying:

```
Terminal> f2py -c wave2D_u0_loop_f77.pyf --build-dir build_f77 \
          -DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_f77.f
```

Efficiency of translating to Fortran

- Same efficiency (in this example) as Cython and C
- About 5 times faster than vectorized numpy code
- > 1000 faster than pure Python code

Migrating loops to C via Cython

- Write the advance function in pure C
- Use Cython to generate C code for calling C from Python
- Full manual control of the translation to C

The C code

- numpy arrays transferred to C are one-dimensional in C
- Need to translate [i,j] indices to single indices

```

/* Translate (i,j) index to single array index */
#define idx(i,j) (i*(Ny)+j)

void advance(double* u, double* u_1, double* u_2, double* f,
            double Cx2, double Cy2, double dt2,
            int Nx, int Ny)
{
    int i, j;
    /* Scheme at interior points */
    for (i=1; i<Nx-1; i++) {
        for (j=1; j<Ny-1; j++) {
            u[idx(i,j)] = 2*u_1[idx(i,j)] - u_2[idx(i,j)] +
                           Cx2*(u_1[idx(i-1,j)] - 2*u_1[idx(i,j)] + u_1[idx(i+1,j)]) +
                           Cy2*(u_1[idx(i,j-1)] - 2*u_1[idx(i,j)] + u_1[idx(i,j+1)]) +
                           dt2*f[idx(i,j)];
        }
    }
}

```

The Cython interface file

```

import numpy as np
cimport numpy as np
cimport cython

def extern from "wave2D_u0_loop_c.h":
    void advance(double* u, double* u_1, double* u_2, double* f,
                double Cx2, double Cy2, double dt2,
                int Nx, int Ny)

@cython.boundscheck(False)
@cython.wraparound(False)
def advance_cwrap(
    np.ndarray[double, ndim=2, mode='c'] u,
    np.ndarray[double, ndim=2, mode='c'] u_1,
    np.ndarray[double, ndim=2, mode='c'] u_2,
    np.ndarray[double, ndim=2, mode='c'] f,
    double Cx2, double Cy2, double dt2):
    advance(&u[0,0], &u_1[0,0], &u_2[0,0], &f[0,0],
            Cx2, Cy2, dt2,
            u.shape[0]-1, u.shape[1]-1)
    return u

```

Building the extension module

Compile and link the extension module with a setup.py file:

```

from distutils.core import setup
from distutils.extension import Extension
from Cython.Distutils import build_ext

sources = ['wave2D_u0_loop_c.c', 'wave2D_u0_loop_c_cy.pyx']
module = 'wave2D_u0_loop_c_cy'
setup(
    name=module,
    ext_modules=[Extension(module, sources,
                           libraries=[]), # C libs to link with
                ],
    cmdclass={'build_ext': build_ext},
)

Terminal> python setup.py build_ext --inplace

In Python:

import wave2D_u0_loop_c_cy
advance = wave2D_u0_loop_c_cy.advance_cwrap
...
f_a[:, :] = f(xv, yv, t[n])
u = advance(u, u_1, u_2, f_a, Cx2, Cy2, dt2)

```

Migrating loops to C via f2py

- Write the advance function in pure C
- Use f2py to generate C code for calling C from Python
- Full manual control of the translation to C

The C code and the Fortran interface file

- Write the C function advance as before
- Write a Fortran 90 module defining the signature of the advance function
- Or: write a Fortran 77 function defining the signature and let f2py generate the Fortran 90 module

Fortran 77 signature (note intent(c)):

```

subroutine advance(u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny)
  integer(c) advance
  integer Nx, Ny, N
  real*8 u(0:Nx,0:Ny), u_1(0:Nx,0:Ny), u_2(0:Nx,0:Ny)
  real*8 f(0:Nx,0:Ny), Cx2, Cy2, dt2
  f2py intent(in, out) u
  f2py intent(c) u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny
  return
end

```

Building the extension module

Generate Fortran 90 module (wave2D_u0_loop_c_f2py.pyf):
Terminal> f2py -m wave2D_u0_loop_c_f2py \
-h wave2D_u0_loop_c_f2py.pyf --overwrite-signature \
wave2D_u0_loop_c_f2py_signature.f

The compile and build step must list the C files:

Terminal> f2py -c wave2D_u0_loop_c_f2py.pyf \
--build-dir tmp_build_c \
-DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_c.c

Migrating loops to C++ via f2py

- C++ can be used as an alternative to C
- C++ code often applies sophisticated arrays
- Challenge: translate from numpy C arrays to C++ array classes
- Can use SWIG to make C++ classes available as Python classes
- Easier (and more efficient):
 - Make C API to the C++ code
 - Wrap C API with f2py
 - Send numpy arrays to C API and let C translate numpy arrays into C++ array classes